

Declaration of Performance

<p>1. Product type Unique identification code of the product type</p>	<p>RonaScreed 4 Day Overlay Quick Drying Screed</p> <p>Ronacrete Standard Primer</p>
<p>2. Type Batch or serial number or any other element allowing identification of the construction product as required under article 11 (4)</p>	<p>PC024 PC040</p> <p>For Batch Number refer to product label.</p>
<p>3. Intended use or uses of the construction product in accordance with the applicable harmonized technical specification, as foreseen by the manufacture.</p>	<p>BS EN 13813</p> <p>Floor Screed</p>
<p>4. Name, registered trade name Or registered trade name and contact address of the manufacturer as required under article 11 (4)</p>	<p>Ronacrete Ltd. Flex Meadow Harlow Essex, CM19 5TD Tel: 01279 638700</p>
<p>5. Contact Address Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in article 12 (2)</p>	<p>N/A</p>
<p>6. AVCP System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V:</p>	<p>3</p>
<p>7. Notified body (hEN) In case of the declaration of performance(DoP) concerning a construction product covered by a harmonized standard.</p>	<p>BRE Notified body number 1796.</p> <p>Classification of reaction to fire test report number 284915.</p>

Declaration of Performance

<p>8. Notified body (ETA) In case of the declaration of performance concerning a construction product for which a European Technical Assessment (ETA) has been issued.</p>	<p>Not relevant (see note 7)</p>
--	----------------------------------

<p>9. Declared performance</p>	
--------------------------------	--

<u>Essential characteristic</u>	<u>Performance</u>	<u>Test Standard</u>	<u>Harmonised technical specification</u>
Reaction to Fire	A2-s1,d0	Declare value	BS EN 13501-1 + A1
Release of Corrosive Substances	No Release	None	
Capillary Water Absorption	$< 0.40\text{kg} / \text{m}^2 \cdot \text{min}^{0.5}$	$< 0.40\text{kg} / \text{m}^2 \cdot \text{min}^{0.5}$	BS EN 1015-18
Compressive Strength	$\geq \text{C40}$	$\geq \text{C5}$	BS EN 12190
Flexural Strength	$\geq \text{F4}$	$\geq \text{F1}$	BS EN 13892-2
Wear Resistance – BCA method	AR3	$\leq \text{AR6}$	BS EN 13892-4
Dampness Test (headspace)	75% RH at 20°C at 4 days	Declare value	BS 8203 + A1

Declaration of Performance

Dangerous Substances	Refer to Safety Data Sheet		
----------------------	----------------------------	--	--

10.

The performance of the product in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance (DoP) is issued under the sole responsibility of the manufacture identified in point 4.

Signed for and on behalf of the manufacturer by:



J. Prendergast
Laboratory Manager

May 17th 2013

Legal note:

This information is given in good faith based on Ronacrete's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Ronacrete's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Ronacrete reserves the right to change the properties of its products. The proprietary rights must be observe. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

