

SAFETY DATA SHEET RonaFloor Epoxy DPM - Part A

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name RonaFloor Epoxy DPM - Part A

Product number PC485

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses [SU22] Professional uses: Public domain (administration, education, entertainment, services,

craftsmen) [AC4] Stone, plaster, cement, glass and ceramic articles [ERC5] Industrial use resulting in inclusion into or onto a matrix [PROC5] Mixing or blending in batch processes for

formulation of preparations and articles (multistage and/or significant contact) Two-

component, epoxy-based adhesive. Sealant.

1.3. Details of the supplier of the safety data sheet

Supplier Ronacrete Limited

Ronac House Flex Meadow Harlow Essex CM19 5TD

www.ronacrete.co.uk Tel: 01279 638 700 Fax: 01279 638 701

email: sds@ronacrete.co.uk

1.4. Emergency telephone number

Emergency telephone +44 (0) 1279 638700

National emergency telephone UK Consumers NHS 111. Medical professionals - www.toxbase.org

number

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards Not Classified

Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317

Environmental hazards Aquatic Chronic 2 - H411

Classification (67/548/EEC or Xi; R36/38. N; R51/53. R43

1999/45/EC)

2.2. Label elements

RonaFloor Epoxy DPM - Part A

Pictogram





Signal word Warning

Hazard statements H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements P261 Avoid breathing vapour/spray.

P264 Wash contaminated skin thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P321 Specific treatment (see medical advice on this label). P332+P313 If skin irritation occurs: Get medical advice/attention.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention. P362+P364 Take off contaminated clothing and wash it before reuse.

P391 Collect spillage.

P501 Dispose of contents/container in accordance with national regulations.

Contains reaction product: bisphenol-A-(epichlorhydrin), Epoxy resin, oxirane, mono[(C12-14-

alkyloxy)methyl] derivs.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

reaction product: bisphenol-A-(epichlorhydrin)

30-60%

Classification

Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Skin Irrit. 2 - H315 Aquatic Chronic 2 - H411

Epoxy resin 30-60%

CAS number: 55492-52-9

Classification

Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317

Aquatic Chronic 2 - H411

RonaFloor Epoxy DPM - Part A

oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

10-30%

CAS number: 68609-97-2 EC number: 271-846-8

Classification

Skin Irrit. 2 - H315 Skin Sens. 1 - H317

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation Remove person to fresh air and keep comfortable for breathing. Get medical attention if

symptoms are severe or persist.

Ingestion Get medical attention immediately. Show this Safety Data Sheet to the medical personnel.

May cause chemical burns in mouth and throat. Do not induce vomiting.

Skin contact The product contains a sensitising substance. Remove contaminated clothing immediately

and wash skin with soap and water. Get medical attention if symptoms are severe or persist

after washing.

Eye contact Remove any contact lenses and open eyelids wide apart. Rinse immediately with plenty of

water. Continue to rinse for at least 15 minutes. Get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Ingestion Burning sensation in mouth. Severe stomach pain.

Skin contact May cause irritation. Repeated exposure may cause skin dryness or cracking.

Eye contact Causes serious eye damage. A single exposure may cause the following adverse effects:

Severe irritation, burning, tearing and blurred vision.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with foam, carbon dioxide or dry powder.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion

products

Toxic gases or vapours.

5.3. Advice for firefighters

Protective actions during

firefighting

No action shall be taken without appropriate training or involving any personal risk.

Special protective equipment

for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

RonaFloor Epoxy DPM - Part A

Personal precautions Avoid contact with skin, eyes and clothing.

6.2. Environmental precautions

Environmental precautions Dangerous for the environment if discharged into watercourses. Do not discharge into drains

or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

Absorb spillage with non-combustible, absorbent material. Place waste in labelled, sealed

containers.

6.4. Reference to other sections

Reference to other sections For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Wear protective clothing as described in Section 8 of this safety data sheet.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry and cool place.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

8.2. Exposure controls

Protective equipment











Appropriate engineering

controls

Observe any occupational exposure limits for the product or ingredients.

Eye/face protection Wear chemical splash goggles.

Hand protection It is recommended that chemical-resistant, impervious gloves are worn.

Other skin and body

protection

Wear appropriate clothing to prevent any possibility of skin contact.

Hygiene measures When using do not eat, drink or smoke. Wash at the end of each work shift and before eating,

smoking and using the toilet. Take off contaminated clothing and wash it before reuse.

Respiratory protection Respiratory protection must be used if the airborne contamination exceeds the recommended

occupational exposure limit.

Environmental exposure

controls

Keep container tightly sealed when not in use. Store in a demarcated bunded area to prevent

release to drains and/or watercourses.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Liquid.

Colour Colourless.

RonaFloor Epoxy DPM - Part A

Odour Mild.

Initial boiling point and range 200°C @ 760 mm Hg

Flash point 100°C

Relative density 1.12

Solubility(ies) Insoluble in water.

9.2. Other information

Other information None.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity See Section 10.3 (Possibility of hazardous reactions) for further information.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

The following materials may react with the product: Alkalis. Acids. Amines. Strong oxidising

agents.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents. Acids. Alkalis. Amines.

10.6. Hazardous decomposition products

Hazardous decomposition

Toxic gases or vapours.

products

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Inhalation May cause irritation.

Ingestion May cause stomach pain or vomiting. May cause chemical burns in mouth, oesophagus and

stomach.

Skin contact The product contains a sensitising substance. In the event of any sensitisation symptoms

developing, ensure further exposure is avoided. Repeated exposure may cause skin dryness

or cracking. Use appropriate hand lotion to prevent defatting and cracking of skin.

Eye contact This product is strongly irritating. Symptoms following overexposure may include the following:

Severe irritation, burning and tearing. Redness. Pain.

SECTION 12: Ecological Information

12.1. Toxicity

Toxicity The product contains a substance which is toxic to aquatic organisms and which may cause

long-term adverse effects in the aquatic environment.

12.2. Persistence and degradability

RonaFloor Epoxy DPM - Part A

Persistence and degradability The product is not readily biodegradable.

No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential Immiscible with water.

12.4. Mobility in soil

Mobility Not known.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

3

assessment

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods

For small quantities, mix Part A and Part B together thoroughly in the correct proportions. After 7 days the mixture forms a non-hazardous solid for disposal by the appropriate method. Do not allow more than 1 Kg of the mixed material (Part A + Part B) as a reacting mass to remain in the container after mixing. The reaction between Part A and Part B is exothermic, with heat energy given out and a rapid rise in temperature. Pouring the reacting mass onto stone aggregate, or forming a shallow pool with a large surface area will allow the heat energy to dissipate to its surroundings. Where there is an excess of Part A or Part B that cannot be reacted off, this must be disposed of by a licensed waste disposal company in accordance with national guidelines. All containers must be properly labelled and a Safety data sheet provided for the waste disposal company.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 3082

UN No. (IMDG) 3082

UN No. (ICAO) 3082

UN No. (ADN) 3082

14.2. UN proper shipping name

Proper shipping name

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN)

(ADR/RID)

Proper shipping name

(IMDG)

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN)

Proper shipping name (ICAO) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN)

Proper shipping name (ADN) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN)

14.3. Transport hazard class(es)

ADR/RID class 9

ADR/RID classification code M6

ADR/RID label 9

IMDG class 9

RonaFloor Epoxy DPM - Part A

ICAO class/division 9

ADN class 9

Transport labels



14.4. Packing group

ADR/RID packing group III

IMDG packing group III

ADN packing group III

ICAO packing group III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

EmS F-A, S-F

ADR transport category 3

Emergency Action Code •3Z

Hazard Identification Number 90

(ADR/RID)

Tunnel restriction code (E)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Not applicable. **Annex II of MARPOL 73/78**

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation Dangerous Preparations Directive 1999/45/EC.

Dangerous Substances Directive 67/548/EEC.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH) (as amended).

Guidance www.echa.europa.eu

www.hse.gov.uk

Workplace Exposure Limits EH40.

Supplier product information and safety data sheets.

15.2. Chemical safety assessment

RonaFloor Epoxy DPM - Part A

No chemical safety assessment has been carried out.

SECTION 16: Other information

Issued by sds@ronacrete.co.uk

Revision date 06/05/2015

Revision 1

SDS number 4649

Risk phrases in full R36/38 Irritating to eyes and skin.

R38 Irritating to skin.

R43 May cause sensitisation by skin contact.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

Hazard statements in full H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.



SAFETY DATA SHEET RonaFloor Epoxy DPM - Part B

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name RonaFloor Epoxy DPM - Part B

Product number PC485

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses [SU22] Professional uses: Public domain (administration, education, entertainment, services,

craftsmen) [ERC5] Industrial use resulting in inclusion into or onto a matrix [PROC5] Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or

significant contact) [AC4] Stone, plaster, cement, glass and ceramic articles

1.3. Details of the supplier of the safety data sheet

Supplier Ronacrete Limited

Ronac House Flex Meadow Harlow Essex CM19 5TD

www.ronacrete.co.uk Tel: 01279 638 700 Fax: 01279 638 701

email: sds@ronacrete.co.uk

1.4. Emergency telephone number

Emergency telephone +44 (0) 1279 638700

National emergency telephone UK Consumers NHS 111. Medical professionals - www.toxbase.org

number

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards Not Classified

Health hazards Acute Tox. 4 - H302 Acute Tox. 4 - H332 Skin Corr. 1B - H314 Skin Sens. 1 - H317 Repr. 2 -

H361f

Environmental hazards Not Classified

Classification (67/548/EEC or Xn; R20/22. C; R34. Repr. Cat. 3 R62. R43

1999/45/EC)

2.2. Label elements

RonaFloor Epoxy DPM - Part B

Pictogram







Signal word

Danger

Hazard statements

H302+H332 Harmful if swallowed or if inhaled.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction. H361f Suspected of damaging fertility.

Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe vapour/spray. P261 Avoid breathing vapour/spray.

P264 Wash contaminated skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace. P280 Wear protective gloves/protective clothing/eye protection/face protection. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P302+P352 IF ON SKIN: Wash with plenty of water.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P312 Call a POISON CENTER/doctor if you feel unwell. P321 Specific treatment (see medical advice on this label).

P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P362+P364 Take off contaminated clothing and wash it before reuse.

P363 Wash contaminated clothing before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with national regulations.

Contains

benzyl alcohol, 2,4,6-tris(dimethylaminomethyl)phenol, methylamine, 3-aminomethyl-3,5,5-trimethylcyclohexylamine, bisphenol A, 3-aminopropyldimethylamine

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

benzyl alcohol 30-60%

Classification

Acute Tox. 4 - H302 Acute Tox. 4 - H332

RonaFloor Epoxy DPM - Part B

3-aminomethyl-3,5,5-trimethylcyclohexylamine

10-30%

CAS number: 2855-13-2 EC number: 220-666-8

Classification

Skin Corr. 1B - H314 Acute Tox. 4 - H302 Acute Tox. 4 - H312 Skin Sens. 1 - H317 Eye Dam. 1 - H318 Aquatic Chronic 3 - H412

methylamine 10-30%

CAS number: 1477-55-0

Classification

Acute Tox. 4 - H302

Acute Tox. 4 - H312

Acute Tox. 3 - H331

Skin Corr. 1B - H314

Eye Dam. 1 - H318 Skin Sens. 1 - H317

Aquatic Chronic 3 - H412

2,4,6-tris(dimethylaminomethyl)phenol

10-30%

CAS number: 90-72-2 EC number: 202-013-9

Classification

Acute Tox. 4 - H302 Skin Irrit. 2 - H315

Eye Irrit. 2 - H319

bisphenol A 5-10%

Classification

Eye Dam. 1 - H318

Skin Sens. 1 - H317

Repr. 2 - H361f

STOT SE 3 - H335

STOT SE 3 - H335

RonaFloor Epoxy DPM - Part B

3-aminopropyldimethylamine 1-5%

CAS number: 109-55-7 EC number: 203-680-9

Classification

Flam. Liq. 3 - H226 Acute Tox. 4 - H302 Skin Corr. 1B - H314 Skin Sens. 1 - H317 Eye Dam. 1 - H318

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation Remove person to fresh air and keep comfortable for breathing. If breathing stops, provide

artificial respiration. Get medical attention immediately.

Ingestion Rinse mouth thoroughly with water. Do not induce vomiting. Get medical attention. Show this

Safety Data Sheet to the medical personnel.

Skin contact Remove contaminated clothing and rinse skin thoroughly with water. Get medical attention if

irritation persists after washing.

Eye contact Remove any contact lenses and open eyelids wide apart. Rinse immediately with plenty of

water. Continue to rinse for at least 15 minutes. Get medical attention if symptoms are severe

or persist after washing.

Protection of first aiders Care should be taken to avoid contact with contaminants when removing contaminated

clothing. Wear suitable gloves.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation Harmful by inhalation. Symptoms following overexposure may include the following: General

respiratory distress, unproductive cough. May cause respiratory system irritation.

Ingestion This product is corrosive. May cause chemical burns in mouth, oesophagus and stomach.

Skin contact May cause sensitisation by skin contact.

Eye contact Symptoms following overexposure may include the following: Pain or irritation. Prolonged

contact may cause redness and/or tearing.

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with foam, carbon dioxide or dry powder.

Unsuitable extinguishing

Water.

media

5.2. Special hazards arising from the substance or mixture

Specific hazards Toxic gases or vapours.

5.3. Advice for firefighters

RonaFloor Epoxy DPM - Part B

Protective actions during

firefighting

Evacuate area. Do not allow water to contact any leaked material.

Special protective equipment

for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

clothing

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Pregnant or breastfeeding women should not work with this product if there is any risk of

exposure. Avoid contact with skin, eyes and clothing. Avoid inhalation of vapours.

6.2. Environmental precautions

Environmental precautions

Avoid the spillage or runoff entering drains, sewers or watercourses.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely. Flush contaminated area with plenty of water. Control run-off water by containing and keeping it out of sewers and watercourses.

6.4. Reference to other sections

Reference to other sections

For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions

For personal protection, see Section 8. Read label before use. Do not allow contact with water. Avoid inhalation of vapours. Avoid contact with skin, eyes and clothing.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Store in a demarcated bunded area to prevent release to drains and/or watercourses. Store in tightly-closed, original container in a dry, cool and well-ventilated place. Store away from incompatible materials (see Section 10).

7.3. Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

None of the ingredients are listed.

8.2. Exposure controls

Protective equipment











Appropriate engineering

controls

Observe any occupational exposure limits for the product or ingredients. Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit.

Personal protection

Pregnant or breastfeeding women should not work with this product if there is any risk of exposure.

Eye/face protection

Wear tight-fitting, chemical splash goggles or face shield.

RonaFloor Epoxy DPM - Part B

Hand protection Wear protective gloves made of the following material: Rubber (natural, latex).

Other skin and body

protection

Wear appropriate clothing to prevent any possibility of skin contact.

Hygiene measures Provide eyewash station. Do not eat, drink or smoke when using this product. Wash at the

end of each work shift and before eating, smoking and using the toilet.

Respiratory protection Respirator selection must be based on exposure levels, the hazards of the product and the

safe working limits of the selected respirator.

Environmental exposure

controls

Keep container tightly sealed when not in use.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Liquid.

Colour Yellowish.

Odour Amine.

Initial boiling point and range 135°C @ 760 mm Hg

Flash point 86°C

Upper/lower flammability or

explosive limits

Lower flammable/explosive limit: 1.3 Vol % Upper flammable/explosive limit: 13.0 Vol %

Vapour pressure 0.3 hPa @ 20°C

Relative density 1.02 @ 23°C

Solubility(ies) Immiscible with water.

Viscosity 600-1400 mPa s @ 25°C

9.2. Other information

Other information None.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Reacts with water. Alcohols. Alkalis. Amines.

10.2. Chemical stability

Stability Stable under the prescribed storage conditions.

10.3. Possibility of hazardous reactions

Possibility of hazardous

Contact with water liberates toxic gas. Carbon dioxide (CO2).

reactions

10.4. Conditions to avoid

Conditions to avoid Contact with water liberates carbon dioxide causing an increase of pressure inside containers.

This may result in containers exploding.

10.5. Incompatible materials

Materials to avoid Never add water to this product.

10.6. Hazardous decomposition products

RonaFloor Epoxy DPM - Part B

Hazardous decomposition

products

Carbon dioxide (CO2). Toxic gases or vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 606.06

Acute toxicity - dermal

ATE dermal (mg/kg) 5,500.0

Acute toxicity - inhalation

ATE inhalation (vapours mg/l) 12.69

Inhalation Harmful by inhalation. Symptoms following overexposure may include the following: General

respiratory distress, unproductive cough. Upper respiratory irritation.

Ingestion Harmful if swallowed. May cause chemical burns in mouth, oesophagus and stomach.

Skin contact The product contains a sensitising substance. In the event of any sensitisation symptoms

developing, ensure further exposure is avoided. Corrosive. Burns can occur.

Eye contact This product is strongly corrosive. Causes serious eye damage.

SECTION 12: Ecological Information

12.1. Toxicity

Toxicity Not Classified for Environmental

12.2. Persistence and degradability

Persistence and degradability The product is not readily biodegradable.

12.3. Bioaccumulative potential

12.4. Mobility in soil

Mobility No information available.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

This product does not contain any substances classified as PBT or vPvB.

assessment

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

RonaFloor Epoxy DPM - Part B

Disposal methods

For quantities up to 5 kg of Part A, mix with an equal amount of Part B. Heat will evolve from

this

mixture, so pour onto aggregate to increase surface area and allow to harden. Do not leave

the

mixture in the container for longer than 5 minutes. Where there is an excess of Part A or Part

В

that cannot be reacted off, this must be disposed of by a licensed waste disposal company in accordance with national guidelines. All containers must be properly labelled and a Safety

data

sheet provided for the waste disposal company.

SECTION 14: Transport information

General

The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation Dangerous Preparations Directive 1999/45/EC.

Dangerous Substances Directive 67/548/EEC.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH) (as amended).

RonaFloor Epoxy DPM - Part B

Guidance www.echa.europa.eu

www.hse.gov.uk

Supplier product information and safety data sheets.

Workplace Exposure Limits EH40.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Issued by sds@ronacrete.co.uk

Revision date 08/05/2015

Revision 1

SDS number 4665

Risk phrases in full R10 Flammable.

R20/22 Harmful by inhalation and if swallowed. R21/22 Harmful in contact with skin and if swallowed.

R22 Harmful if swallowed. R34 Causes burns.

R36/38 Irritating to eyes and skin. R37 Irritating to respiratory system. R41 Risk of serious damage to eyes.

R43 May cause sensitisation by skin contact.

R52 Harmful to aquatic organisms.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

R62 Possible risk of impaired fertility.

Hazard statements in full H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.
H332 Harmful if inhaled.

H335 May cause respiratory irritation. H361f Suspected of damaging fertility.

H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.